

PACKAGE PRICE

- **Trinity F90+ UAV**
- **PPK**
Allows you to reduce typical GNSS geotagging errors of several meters down to 2-5 cm via auxiliary GNSS data collection in flight. Better accuracy with dramatically reduced additional costs!
- **Anti-Collision-Lights**
Our Trinity F90+ UAV has integrated flashing anti-collision strobe and position lights.
- **Live-Air-Traffic**
Now it is possible to automatically integrate the Live-Air-Traffic-Info into QBase when pingUSB is connected. pingUSB is the world's smallest, lightest and most affordable USB dual-band ADS-B receiver. pingUSB provides high-quality tracking data for use with software such as Virtual Radar Server and services including ADS-B Exchange.
- **iBase**
iBase is a reference GNSS station, it allows for the relative (and at externally georeferenced points absolute) geotagging precision of aforementioned PPK quality via logging the GNSS reference measurements on the ground to later use them in QBase flight data post-processing.
- **QBase - Ground Control Station**
Mission planning software, runs on any Windows PC/Laptop
 - Corridor Planning, Live-Air-Traffic, Resume Mission
- **Remote Controller (RC)**
- **Battery Pack + Battery Charger**
- **Lightweight Transport Case**
- **Warranty (1 year)**
- **Technical Support**

starting at **15.900€** /excl. VAT

TECHNICAL DATA







	LOCKED <60 MINUTES	UNLOCKED 90+ MINUTES ¹
Max. Take-off Weight	5.0 kg (11.0lbs)	5.0 kg (11.0lbs)
Max. Flight Time	<60 min	90+ min ¹
Max. Range = Area	70 km = 500 ha	100 km = 700 ha
Maximum flight altitude (MSL)	4500 m (13123.4 ft) ²	4500 m (13123.4 ft) ²
Command and Control Range	5-7.5 km (3.1-4.7 mi)	5-7.5 km (3.1-4.7 mi)
Payload (with compartment)	max. 700 g (1.54 lbs)	max. 700 g (1.54 lbs)
Optimal Cruise Speed	17 m/s (33 kn)	17 m/s (33 kn)
Wind Tolerance (ground)	up to 9 m/s (17.5 kn) ³	up to 9 m/s (17.5 kn) ³
Wind Tolerance (cruise)	12 m/s (23.3 kn)	12 m/s (23.3 kn)
Operating temperature range	-12°C to 50°C (10.4°F to 122°F)	-12°C to 50°C (10.4°F to 122°F)
Wingspan	2.394 m (7.85 ft)	2.394 m (7.85 ft)
Transport Case Dimension	1002x830x270 mm (39.4x32.7x10.6 inch)	1002x830x270 mm (39.4x32.7x10.6 inch)
Transport Case Weight (3 batteries)	22.3 kg (49.1 lbs)	22.3 kg (49.1 lbs)

¹ Subject to export regulation, may require export permission.


² Please be aware that the flight time and max. wind tolerance are reduced with increasing flight altitude. Depending on the weather conditions; tested at 15°C (59°F). For further details read the user manual chapter 3.1.

³ Please be aware that the max. wind tolerance is reduced with increasing flight altitude.

OPTION

	Trinity F90+ Art.: 4260574661427	15.900 €
	Trinity F90+ ADS-B Art.: 4260574661748 Mandatory to buy the Mode S ADS-B out Transponder	15.900 €
	DLSII Kit (Plug & Play) for enhanced light calibration Art.: 4260574663094 Mandatory for MicaSense camera to achieve optimal results	850 €
	Calibrated Reflectance Panel (CRP) Art.: 4260574660758 Mandatory for MicaSense camera to achieve optimal results	450 €
	Ping5S MODE S ADS-B out Transponder Art.: 4260574662059	2.590 €
	Ping5S MODE S ADS-B out Transponder Art.: 4260574662059 (subsequent upgrade)	3.590 €

ACCESSORIES




	Payload Compartment 3D Print payload (90 g) including multi-payload interface board to integrate pre-defined cameras. Excl. cameras.	
	Sony RX1RII Ready Art.: 4260574662134	740 €
	MicaSense RedEdge-MX Dual Ready Art.: 4260574662127	790 €
	MicaSense RedEdge-MX Ready Art.: 4260574662141	740 €
	MicaSense Altum Ready Art.: 4260574662097	950 €
	Signal Stickers Art.: 4260574661960 4 pieces of signal stickers. 2x green (top & bottom) for left wing, 2x red (top & bottom) for right wing).	40 €
	Additional Training Art.: 1-60-7 Training for two persons. Improve your mission planning and /or learn how to operate your Quantum product properly.	1.000 € (per day)
	Post-Processing Basic Art.: 1-60-8 Improve your photogrammetric analysis and learn how to make the necessary adjustments for the expected accuracy.	1.000 € (per day)
	Spare Parts & Service Please get in touch with us directly. Our support team will create an individual repair or service solution for you depending on your request. Please contact support@quantum-systems.com	

REPLACEMENT COVERAGE PLAN

	Replacement Coverage Plan #1 Art.: 4260574663124 Purchase with Trinity	3.490 €
	Replacement Coverage Plan #2 Art.: 4260574663131 Purchase with Trinity	6.490 €
	Replacement Coverage Plan #1 Art.: 4260574663148 Subsequent Purchase or Extension	3.990 €
	Replacement Coverage Plan #2 Art.: 4260574663155 Subsequent Purchase or Extension	6.990 €
	Replacement Coverage Plan #1 Art.: 4260574663162 RCP Extension (If the drone replacement was not claimed in the previous year)	1.995 €
	Replacement Coverage Plan #2 Art.: 4260574663179 RCP Extension (If the drone replacement was not claimed in the previous year)	3.495 €

COMPARTMENTS

All sensors are delivered integrated in the 3D Print Payload Compartment including the multifunctional interface board.

	Sony UMC Art.: 4260574661571	2.290 €
	Sony UMC-R10C 20.1 MP Sensor with 16 mm fixed focal length.	
	Sony RX1R II Art.: 4260574661588	5.450 €
	CMOS full format sensor and fixed focal length lens. 42.4 MP resolution	
	MicaSense RedEdge-MX Art.: 4260574661595	5.590 €
	Captures five narrow spectral bands; Excl. DLS II and Calibrated Reflectance Panel (CRP).	
	MicaSense Dual Camera Kit Art.: 4260574662073	10.740 €
	MicaSense RedEdge-MX + RedEdge-MX Blue Synchronized capture of all 10 bands for pixel aligned imagery. Excl. DLS II and CRP.	
	MicaSense RedEdge-MX Blue Ready Art.: 4260574662103	5.940 €
	Ready for MicaSense RedEdge-MX camera. New coastal blue band, a new green band and three new bands in the red to red-edge region of the spectrum. Excl. DLS II and CRP. Incl. RedEdge-MX Blue. Excl. RedEdge-MX	
	Double Payload Sony UMC + MicaSense RedEdge-MX Art.: 4260574661601	6.990 €
	Excl. DLS II and CRP.	
	Sony UMC + MicaSense RedEdge-MX Ready Art.: 4260574662080	2.390 €
	Ready for MicaSense RedEdge-MX camera. Incl. Sony UMC. Excl. Red-Edge-MX.	
	MicaSense Altum Art.: 4260574661977	11.450 €
	Altum integrates a radiometric thermal camera with five high-resolution narrow bands, producing advanced thermal, multispectral and high-resolution imagery in one flight for advanced analytics. Excl. DLS II and CRP.	
	Qube 240 LiDAR Art.: 4260574663049 (Pre-Order) with CloudStation Q240	50.000 €
	CloudStation Strip Adjustment Module Art.: 4260574663056 (annual license)	1.600 €
	Applanix POSPac UAV Art.: 4260574663063 (annual subscription)	2.500 €
	Applanix POSPac UAV Art.: 4260574663070 (perpetual license)	8.500 €

SPARE PARTS

Elevator* Art.: 4260574661410	99 €
Battery Pack* Art.: 4260574661335 Capacity 12.000 mAh	640 €
QS Battery Charging Station + Power Supply incl. 12V Clamp Power Cords	429 €
Easily Charge / Discharge your Trinity F90+ Battery packs. EU (Type F) Art.: 4260574660666 US (Type B) Art.: 4260574660673 UK (Type I) Art.: 4260574660680	
Outside wing*	each 330 €
(left Art.: 4260574661397 or right Art.: 4260574661380)	
Strobe Lights* Art.: 4260574661052 RED, GREEN and WHITE, incl. charger, excl. micro-USB cable	50 €

*Can be replaced by the customer.
Modifications and 3rd party products will void warranty.